

# AXIS M4216-V Dome Camera

## Varifocal 4 MP dome with deep learning

The compact and discreet AXIS M4216-V delivers great images in challenging light conditions. With a deep learning processing unit (DLPU), it's possible to take advantage of intelligent applications based on deep learning on the edge. Furthermore, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis devices on your network. Designed to blend seamlessly into any environment, the camera can be repainted and offers a wide range of accessories for discreet monitoring. It features an HDMI port and offers the flexibility to add audio and I/O connectivity using AXIS T61 Audio and I/O Interface.

- > [Great image quality in 4 MP](#)
- > [Varifocal lens with remote zoom and focus](#)
- > [WDR and Lightfinder](#)
- > [Support for analytics with deep learning](#)
- > [HDMI output for public viewing monitors](#)



# AXIS M4216-V Dome Camera

Camera	
Image sensor	1/2.7" progressive scan RGB CMOS
Lens	Varifocal, 3–6 mm, F1.9 – 2.7 Horizontal field of view: 100°–45° Vertical field of view: 72°–34° Remote focus and zoom, fixed iris
Day and night	Automatic IR-cut filter
Minimum illumination	With Lightfinder: Color: 0.18 lux at 50 IRE F2.0 B/W: 0.03 lux at 50 IRE F2.0
Shutter speed	1/37500 s to 1/5 s
Camera angle adjustment	Pan ±180°, tilt –40 to +65°, rotation ±105° Can be directed in any direction and see the wall/ceiling
System on chip (SoC)	
Model	CV25
Memory	1024 MB RAM, 512 MB Flash
Compute capabilities	Deep learning processing unit (DLPU)
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main and High Profiles Motion JPEG
Resolution	2304x1728 to 320x240
Frame rate	25/30 fps with power line frequency 50/60 Hz
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/MBR H.264/H.265 HDMI
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate
HDMI output	HDMI 1080p (16:9) @25/30 fps (50/60 Hz) HDMI 720p (16:9) @50/60 fps (50/60 Hz)
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, motion-adaptive exposure, WDR: up to 110 dB depending on scene, text and image overlay, mirroring of images, privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format
Pan/Tilt/Zoom	Digital PTZ
Audio	
Audio input/output	Two-way audio connectivity via optional AXIS T61 Audio and I/O Interfaces with portcast technology
Network	
Security	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, Axis Edge Vault with Axis device ID
Supported protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS <sup>a</sup> , TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTPC, ICMP, DHCP, ARP, SOCKS, SSH, HDMI, LLDP, CDP, MQTT v3.1.1, Link-Local address (ZeroConf)
System integration	
Application Programming Interface	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> One-click cloud connection ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile M, ONVIF <sup>®</sup> Profile S, and ONVIF <sup>®</sup> Profile T, specification at <a href="http://onvif.org">onvif.org</a>
Event conditions	Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: manual trigger, virtual input, digital input via AXIS T61 Audio and I/O Interfaces with portcast technology

	MQTT subscribe MQTT subscribe Scheduled and recurring: scheduled event Video: live stream open
Event actions	MQTT publish Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text, zoom preset, day/night mode Pre- and post-alarm video or image buffering for recording or upload Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email External output activation via AXIS T61 Audio and I/O Interfaces with portcast technology MQTT publish
Data streaming	Event data
Built-in installation aids	Remote zoom, remote focus
Analytics	
AXIS Object Analytics	Object classes: humans, vehicles (types: cars, buses, trucks, bikes) Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
Applications	Included AXIS Object Analytics, AXIS Video Motion Detection, AXIS Face Detector, active tampering alarm Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
General	
Casing	IP42 water- and dust-resistant, IK08 impact-resistant, polycarbonate and aluminum casing with hard-coated dome Encapsulated electronics Color: white NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.
Sustainability	PVC free, BFR/CFR free, 43% recycled plastics
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2 Typical 2.8 W, max 4.4 W
Connectors	RJ45 10BASE-T/100BASE-TX PoE HDMI type D Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)
Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC CISPR 24, CISPR 35, EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN/UL 62368-1, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-6, IEC/EN 60529 IP42, IEC/EN 62262 IK08 Network NIST SP500-267
Dimensions	Height: 71 mm (2.8 in) ø 121 mm (4.76 in)

<b>Weight</b>	350 g (0.77 lb)	<b>Video management software</b>	AXIS Companion, AXIS Camera Station and video management software from Axis Application Development Partners. For more information, see <a href="http://axis.com/vms">axis.com/vms</a>
<b>Included accessories</b>	Installation guide, Windows® decoder 1-user license	<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Japanese, Korean, Portuguese, Simplified Chinese, Traditional Chinese
<b>Optional accessories</b>	AXIS TM3207 Recessed Mount AXIS T61 Audio and I/O Interface Series AXIS T94C01L Recessed Mount AXIS T94C01U Universal Mount AXIS T94C01M J-Box/Gang Box Plate AXIS M42 Casing A Black 4P AXIS M42 Smoked Dome A 4P AXIS T91A33 Lighting Track Mount AXIS T91A23 Tile Grid Ceiling Mount AXIS TM3101 Pendant Wall Mount AXIS Surveillance Cards For more accessories, see <a href="http://axis.com">axis.com</a>	<b>Warranty</b>	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

Environmental responsibility:  
[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)