

# Delock DisplayPort cable male straight to male 90° upwards angled 8K 60 Hz 1 m without latch

## Description

This DisplayPort cable by Delock is used to connect devices with a DisplayPort interface, such as monitors, projectors or televisions, to a PC or laptop. Supporting a maximum bandwidth of 32.4 Gb/s, content can be displayed in 8K Ultra HD (7680 x 4320 @ 60 Hz) resp. 5K (5120 x 2880 @ 120 Hz) and 4K Ultra HD (3840 x 2160 @ 240 Hz) resolution. The high-quality, triple-shielded cable also significantly improves the quality of audio transmissions with a sampling rate of up to 1536 kHz.

## Slim plug

Thanks to the missing latch, the plugs are a bit slimmer than standard DisplayPort plugs, so several ports can be used simultaneously. In addition, the plugs can be removed more easily from hard-to-reach DisplayPort ports, e.g. on the rear side of a monitor.



## Specification

- Connectors:
  - 1 x DisplayPort male >
  - 1 x DisplayPort male angled
- DisplayPort 1.4 specification
- Downwards compatible to DisplayPort 1.3, 1.2 and 1.1
- Pin 20 not connected
- Cable gauge: 30 AWG
- Cable diameter: ca. 5.7 mm
- Copper conductor
- Triple shielded cable
- Contacts gold-plated
- Transmission of audio and video signals
- Data transfer rate up to 32.4 Gbps
- Resolution up to:
  - Display with DSC support: 7680 x 4320 @ 60 Hz
  - Display without DSC support: 7680 x 4320 @ 30 Hz
  - (depending on the system and the connected hardware)
- Supports Display Stream Compression 1.2 (DSC)
- Supports HDR
- Supports HDCP 1.4 and 2.2
- Supports HBR3 (8.1 Gbps) data rate
- Up to 32 audio channels for speakers
- Up to 1536 kHz audio sampling rate
- Supports colour sampling in 4:4:4, 4:2:2 and 4:2:0 format
- Colour: black
- Length incl. connectors: ca. 1 m

## System requirements

- A free DisplayPort interface

## Package content

- DisplayPort cable

## Item no. 87143

EAN: 4043619871438

Country of origin: China

Package: Retail Box

Images



General	
Specification:	HDCP 1.4 HDCP 2.2 DisplayPort 1.4 HDR10
Style:	angled 90°
Interface	
Connector 1:	1 x DisplayPort male
Connector 2:	1 x DisplayPort male
Technical characteristics	
Data transfer rate:	32.4 Gb/s
Maximum screen resolution:	7680 x 4320 @ 60 Hz
Physical characteristics	
Cable diameter:	5.7 mm
Pin finishing:	gold-plated
Conductor material:	copper
Conductor gauge:	30 AWG
Shielding:	triple
Length:	1 m
Colour:	black