

# Delock Serial Cable RS-232 D-Sub9 male to male with narrow plug housing 3 m

## Description

This serial cable by Delock is suitable as a **connection cable** for modem, printer, measuring instruments, converters, RS-232 hubs, patch panels etc.

### Mini D-Sub9 connector

These cables fit on any RS-232 port, as the mini D-Sub9 connectors (44 x 33.3 x 15 mm) are small and compact. In this way, RS-232 connections can be used directly adjacent to each other.



3 m

## Specification

- Connectors:  
1 x serial D-Sub9 male with screws >  
1 x serial D-Sub9 male with screws
- Cable gauge: 28 AWG
- Pin assignment: 1:1
- Colour: black
- Insulator: PVC
- Screw type: #4-40 UNC
- Cable diameter: ca. 5 mm
- Cable length incl. connectors: ca. 3 m

## Item no. 86575

EAN: 4043619865758

Country of origin: China

Package: • Zip poly bag

## System requirements

- A free D-Sub9 female

## Package content

- Cable

## Images



General	
Specification:	RS-232 (EIA / TIA)
Style:	Connection cable Mini Sub-D9
Interface	
Connector 1:	1 x serial Sub-D 9 male with screws
Connector 2:	1 x serial Sub-D 9 male with screws
Technical characteristics	
Data transfer rate:	up to 921.6 Kbps
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Physical characteristics	
Cable type:	AWM Style 2464 28 AWG 80 °C 300 V VW-1
Cable diameter:	5 mm
Cable length incl. connector:	3 m
Pin finishing:	gold-plated
Conductor material:	Copper tinned
Conductor gauge:	28 AWG
Screw type:	#4-40 UNC
Shielding:	Aluminum foil
Colour:	black
Cable jacket material:	PVC
Safety of Flammability:	VW-1