

Delock Converter Ethernet LAN > Serial RS-232

Description

The Delock Ethernet to RS-232 converter by Delock enables you to integrate and control serial devices based on RS-232 via your network.



Specification

- Connector:
 - Host: 1 x RJ45 female
 - Device: 1 x Sub-D 9 pin Serial RS-232 male
 - 1 x DC 1.3 x 3.5 mm for power supply
 - 1 x 2 pin terminal block for power supply
- Data transfer rate:
 - Fast Ethernet up to 100 Mb/s
 - RS-232 up to 460 Kb/s
- LED indicators for status TX / RX
- Reset bottom
- ± 15 kV ESD protection for all signal pins
- Power consumption: 97 mA / 2328 mW
- Power supply with 10 ~ 30 V via terminal block or DC port
- Dimension DC port: 1,35 x 3,5 mm (ground outside, plus inside)
- Operating temperature: - 25° ~ 65° C
- Storage temperature: - 40° ~ 85° C
- Relative humidity: 5 ~ 95 % (not condensing)
- Housing: plastic
- Dimension (LxWxH): ca. 94 x 54 x 22 mm

System requirements

- Windows XP/XP-64/Vista/Vista-64/7/7-64/8/8-64
- One free Ethernet port

Package content

- Converter
- Mounting set for DIN rail
- Driver CD
- User manual

Item No. 62504

EAN: 4043619625048

Country of origin: Taiwan, Republic of China

Package: Box



Images

