

Delock USB 3.0 Adapter Pin Header female to internal Key A female

Description

This adapter by Delock converts the internal USB pin header male into the internal USB key A female. Various cables can be connected to the adapter, to provide either one USB Type-C™ or two USB Type-A interface.

Active adapter

Due to the built-in chipset, USB Type-C™ functions such as channel configuration (CC1 and CC2) can be used.



Specification

- Connectors:
 - 1 x 19 pin SuperSpeed USB (USB 3.2 Gen 1) pin header female
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) key A 20 pin female
- Chipset: Etron EJ179V
- Data transfer rate up to 5 Gbps
- Electrical power: max. 4.5 watt (5 V / 900 mA)
- Dimensions (LxWxH): ca. 28.5 x 22.4 x 11.1 mm

System requirements

- Linux Kernel 4.9 or above
- Windows 8.1/8.1-64/10/10-64
- Motherboard with a free 19 pin USB 3.0 pin header male

Package content

- Adapter

Item no. 66432

EAN: 4043619664320

Country of origin: China

Package: • Zip poly bag



General

Specification:	USB 3.0
Supported operating system:	Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.9 or above

Interface

Connector 1:	1 x 20 pin USB 3.0 pin header female
Connector 2:	1 x SuperSpeed USB (USB 3.2 Gen 1) key A 20 pin female

Technical characteristics

Chipset:	Etron EJ179V
Data transfer rate:	USB 3.0 up to 5 Gb/s

Physical characteristics

Length:	28.5 mm
Width:	22.4 mm
Height:	11.1 mm