

LC1200P V2.52

Platinum Series ATX power supply with 1200 W

The LC1200P V2.52 is an 80 PLUS® PLATINUM certified, fully modular ATX power supply, which offers your system high stability and performance.

- ATX form factor
- 1200 W
- 120 mm fan
- full modular cable management
- black ribbon cable
- 80 PLUS® PLATINUM certified
- high efficiency up to 92 %
- full range: 110 - 240 V
- DC-to-DC technology
- high-performance +12 V rail (100 A)
- 2x PCI-Express 5.0 12+4 pin
- 8x PCI-Express 6+2 pin



Technical specification - LC1200P V2.52

Dimension (PSU):	86 x 180 x 150 mm
Dimension (package):	120 x 295 x 225 mm
Weight (product/overall):	/ kg
Fan:	120 mm
Connectors:	
20+4 pin mainboard:	1x 650 mm
4+4 pin mainboard 12 V (8 pin EPS):	2x 650 mm
4 pin mainboard 12 V:	1x 800 mm
PCI-Express 5.0 12+4 pin:	2x 650 mm
PCI-Express 6+2 pin:	4x 675 mm / 4x 750 mm
SATA:	5x 500 mm / 5x 650 mm / 5x 800 mm / 5x 950 mm
PATA:	2x 500 mm / 2x 650 mm / 1x 800 mm
FDD:	1x 100 mm

Form factor:	ATX, Version 2.52
PFC:	active
Full range:	110 - 240 V
Standby:	< 0,5 W
Efficiency:	up to 92 %
Certified:	80 PLUS® PLATINUM
Security circuitries:	OVP (Over-Voltage Protection), OCP (Over-Current Protection), OPP (Over-Power Protection), SCP (Short-Circuit Protection), UVP (Under-Voltage Protection)
Material:	metal, plastic
Mark of conformity:	CE, TÜV
Colour:	black
Barcode:	4260070129827
Manufacturer code:	LC1200P V2.52

Power rating:

AC Input	110-240 V ~ 15 A 47-60 Hz Active PFC ATX V2.52				
DC Output	+3,3 V	+5 V	+12 V	-12 V	+5 Vsb
Output Current	20 A	20 A	100 A	0,3 A	3 A
Combined Output Power	100 W	1200 W	3,6 W	15 W	
Max. Combined	1200 W				

*How to use:
Option 1: 20x SATA & 3x PATA
Option 2: 16x SATA & 6x PATA